

IN THE CLAIMS

1. (Currently Amended) A method for forming a data table stored in memory, the data table forming a library index of storage locations to electronic digital content, the method comprising the steps of:

~~—receiving an encrypted file from storage wherein the file has a beginning, an end and a trailer section located just prior to the end;~~

~~—reading a predetermined distance into the file to retrieve an identifier placed at a predetermined position;~~

~~—decrypting a identifier with a first decrypting key;~~

~~—determining if the identifier is valid and if the identifier is valid then performing the steps of:~~

~~—reading the trailer section from the file;~~

~~decrypting the trailer at least a section of a file with the first decrypting key, wherein the first decrypting key is formed as a combination of a base key, a time-stamp, and an update number so as to uniquely correspond to both a given time and a given update in the section of the file;~~

~~determining if there are any updates in the trailer-section of the file to any data items that form a library index of storage locations to electronic digital content and if there are no updates to the trailer-section then performing the steps of:~~

~~decrypting, with the first decrypting key, a reference table containing one or more data-table-location indicators for storing the data items in a data table with the first decrypting key;~~

~~—decrypting one or data items with the first decrypting key; and~~

~~populating the data table with the data items at locations specified by the location indicators in the reference table with data.~~

2. (Original) The method according to claim 1, wherein the step of populating the data table includes populating the data table in a tamper resistant environment.

3. (Currently Amended) The method according to claim 1, further comprising the steps of retrieving from a key database at least one of:

~~retrieving a base key from a key database; and~~
~~retrieving a time-stamp from the database file; and~~
an update number

~~forming the first decrypting key as a combination of the base key and the timestamp.~~

4. (Currently Amended) The method according to claim 1, wherein the step of determining if there are any updates in the trailer-section of the file includes;

getting an offset to an update reference table;

decrypting the update reference table containing one or more ~~data-table~~ location indicators for updates to the data items with the first decrypting key;

~~decrypting one or more update data items with the first decrypting key; and~~

populating the data table with the updates to the data items at locations specified in the update reference table with the updates to the data items.

Claims 5-9 (Withdrawn)

10. (Currently Amended) A method for forming a data table stored in memory, the data table forming a library index of storage locations to electronic digital content, the method comprising the steps of:

~~retrieving an encrypted file from storage wherein the file has a beginning, an end and trailer section located just prior to the end;~~

~~reading from the end of the file, a predetermined distance, to read an identifier placed at a predetermined position;~~

~~decrypting a token with a first decrypting key;~~

~~determining if the token is valid and if the token is valid then performing the steps of:~~

SOM920010003US1

3 of 14

09/884,618

~~reading the trailer section from the file;~~

decrypting the trailer section of a file with the first decrypting key, wherein the first decrypting key is formed as a combination of a base key, a time-stamp, and an update number so as to uniquely correspond to both a given time and a given update in the trailer section of the file;

determining if there are any updates in the trailer section of the file to any data items that form a library index of storage locations to electronic digital content and if there are no updates ~~to the trailer section~~ then performing the steps of:

decrypting, with the first decrypting key, a reference table containing one or more data-table-location indicators for storing the data items in a data table with the first decrypting key;

decrypting one of the data items with the first decrypting key; and

populating the data table with the data items at locations specified by the location indicators in the reference table with data.

11. (Currently Amended) A computer readable medium containing programming instruction for forming a data table stored in memory, the data table forming a library index of storage locations to electronic digital content, the programming instructions comprising:

~~receiving an encrypted file from storage wherein the file has a beginning, an end and a trailer section located just prior to the end;~~

~~reading a predetermined distance into the file to retrieve an identifier placed at a predetermined position;~~

~~decrypting a identifier with a first decrypting key;~~

~~determining if the identifier is valid and if the identifier is valid then performing the steps of:~~

~~reading the trailer section from the file;~~

decrypting the trailer at least a section of a file with the first decrypting key, wherein the first decrypting key is formed as a combination of a base key, a time-

stamp, and an update number so as to uniquely correspond to both a given time and a given update in the section of the file;

determining if there are any updates in the trailer-section of the file to any data items that form a library index of storage locations to electronic digital content and if there are no updates to the trailer-section then performing the steps of:

decrypting, with the first decrypting key, a reference table containing one or more data-table-location indicators for storing the data items in a data table with the first decrypting key;

~~decrypting one or data items with the first decrypting key; and~~
populating the data table with the data items at locations specified by the location indicators in the reference table with data.

12. (Original) The computer readable medium according to claim 11, wherein the programming instruction of populating the data table includes populating the data table in a tamper resistant environment.

13. (Currently Amended) The computer readable medium according to claim 11, further comprising the programming instruction of retrieving from a key database at least one of:

~~retrieving a base key from a key database;~~
~~retrieving a time-stamp from the database file; and~~
an update number.

~~forming the first decrypting key as a combination of the base key and the timestamp~~

14. (Currently Amended) The computer readable medium according to claim 11, wherein the programming instruction of determining if there are any updates in the trailer-section of the file includes::

getting an offset to an update reference table;

decrypting the update reference table containing one or more ~~data table~~ location indicators for updates to the data items with the first decrypting key;
~~decrypting one or more update data items with the first decrypting key; and~~
populating the data table with the updates to the data items at locations specified in the update reference table with the updates to the data items.

15. (Currently Amended) An end user information processing system comprising:

a data table stored in memory, the data table forming a library index of storage locations to electronic digital content;

~~—— an encrypted file received receiving from storage wherein the file has a beginning, an end and trailer section located just prior to the end;~~

~~—— an identifier placed at a predetermined distance in the file;~~

a first decrypting key for decrypting a identifier at least a section of a file, wherein the first decrypting key is formed as a combination of a base key, a time-stamp, and an update number so as to uniquely correspond to both a given time and a given update in the section of the file;

~~means for determining if the identifier is valid and if the identifier is valid then means for determining if there are any updates in the trailer section of the file to one or more data items that form the library index of storage locations to electronic digital content and wherein the trailer section has been decrypted with the first decrypting key section, and if there are any updates in the trailer section, if there are no updates then~~

decrypting, with the first decrypting key, a reference table containing one or more location indicators for storing the data items in a data table; and

populating the data table with the data items at locations specified by the location indicators in the reference table ~~with data~~.

16. (Currently Amended) The end user information processing system according to claim 15, wherein the means for ~~determining if the identifier is valid further includes~~

populating the data table includes populating the data table in a tamper resistant environment.

17. (New) The method according to claim 1, further comprising decrypting one or data items with the first decrypting key.

18. (New) The method according to claim 4, further comprising decrypting the updates to the data items with the first decrypting key.

19. (New) The computer readable medium according to claim 11, further comprising decrypting one or data items with the first decrypting key.

20. (New) The end user information processing system according to claim 15, further comprising decrypting the updates to the data items with the first decrypting key.

21. (New) The end user information processing system according to claim 15, wherein the means for populating further comprises

getting an offset to an update reference table;

decrypting the update reference table containing one or more location indicators for updates to the data items with the first decrypting key; and;

populating the data table with the updates to the data items at locations specified in the update reference table with the updates to the data items.

22. (New) The end user information processing system according to claim 20, further comprising decrypting the updates to the data items with the first decrypting key.